



- Συμπαγές ελαστικό υπεραπορροφητικό κραδασμών
- Ζάντα από χυτοσίδηρο ή κατεργασμένο χάλυβα
- Ρουλεμάν άξονα:

☐☐ σφαιρικό [S]



- Soft elastic black rubber
- Cast iron or steel fabricated center
- Axle bearing:

☐☐ ball [S]



						CODE
125	50	20	60	☐☐	225	WL-125-XE.S20
150	50	20	60	☐☐	250	WL-150-XE.S20
160	50	20	60	☐☐	300	WL-160-XE.S20
180	50	20	60	☐☐	325	WL-180-XE.S20
	50	25	60	☐☐	325	WL-180-XE.S25
200	50	20	60	☐☐	350	WL-200-XE.S20
	50	25	60	☐☐	350	WL-200-XE.S25
200S	75	25	90	☐☐	500	WL-200S-XE.S25
230	50	25	60	☐☐	450	WL-230-XE.S25
	50	30	60	☐☐	450	WL-230-XE.S30
250	50	25	60	☐☐	450	WL-250-XE.S25
250S	80	25	85	☐☐	675	WL-250S-XE.S25
	80	30	85	☐☐	675	WL-250S-XE.S30
280S	75	30	85	☐☐	725	WL-280S-XE.S30
	75	35	85	☐☐	725	WL-280S-XE.S35
300S	80	25	85	☐☐	750	WL-300S-XE.S25
300X	100	35	120	☐☐	975	WL-300X-XE.S35
	100	40	120	☐☐	975	WL-300X-XE.S40
360	85	35	90	☐☐	1050	WL-360-XE.S35
	85	40	90	☐☐	1050	WL-360-XE.S40
400	75	35	90	☐☐	1000	WL-400-XE.S35
425	150	40	160	☐☐	1800	WL-425-XE.S40
500	85	40	90	☐☐	1300	WL-500-XE.S40
550	120	45	130	☐☐	1825	WL-550-XE.S45
550S	160	50	170	☐☐	2250	WL-550S-XE.S50
620	200	50	210	☐☐	3000	WL-620-XE.S50